

# HSL-TB32-MD

## 32-CH Separate I/O Terminal Base



### Specifications


■ General Description	Separate I/O wiring connection for HSL I/O modules	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
	Every I/O points uses 3-pin connector		■ Power Supply
	Pin definition is signal/ground/power (from left to right)	■ Dimensions	129 x 107 x 47.5 mm (W x L x H)
	Separate fuse protection for each I/O points (jumper selection)		
	Supports common/separate DC power supply (jumper selection)		
	Terminator resistor on board (jumper selection)		
	Interlocking design for rugged installation		
	Power LED indicator		
	DIN rail mounting		
	Power and ground included for each signal channel		

### Support Modules

- HSL-DI16DO16-M-NN/-PN/-PP/-NP
- HSL-DI32-M-N/P
- HSL-DO32-M-N/P

# HSL-TB32-M-DIN

## 32-CH I/O Terminal Base



### Specifications


■ General Description	Field I/O wiring connection for HSL I/O modules	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
	Spring terminal for easy field wiring		■ Power supply
	Power and ground included for each signal channel	■ Dimensions	128.5 x 85.5 x 108 mm (W x L x H)
	Interlocking design for rugged installation		
	Power LED indicator		
	DIN rail mounting		
	Terminator resistor on board		

### Support Modules

- HSL-DI16DO16-M-NN/-PN/-PP/-NP
- HSL-DI32-M-N/P
- HSL-DO32-M-N/P
- HSL-R8DI16-M-N/-P
- HSL-AI16AO2-M-VV/-AV

# HSL-TB32-U-DIN

## 32 Points Universal Terminal Base



### Specifications

■ General Description	Field I/O wiring connection for HSL I/O modules	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
	Spring terminal for easy field wiring		■ Power Supply
	Power and ground included for each signal channel	■ Dimensions	126 x 120.1 x 107.3 mm (W x L x H)
	Interlocking design for rugged installation		
	Power LED indicator		
	DIN rail mounting		
	Terminator resistor on board		

### Support Modules

- HSL-DI16DO16-DB-NN/-PN/-PP/-NP
- HSL-DI32-DB-N/P
- HSL-DO32-DB-N/P

# HSL-TB64

## 64 Points High Density Terminal Base



### Specifications

■ General Description	Field I/O wiring connection for HSL I/O modules	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
	Spring terminal for easy field wiring		■ Power Supply
	Power and ground included for each signal channel	■ Dimensions	168.7 x 120.1 x 107.1 mm (W x L x H)
	Interlocking design for rugged installation		
	Power LED indicator		
	DIN rail mounting		
	Terminator resistor on board		

### Support Modules

- HSL-DI16DO16-DB-NN/-PN/-PP/-NP
- HSL-DI32-DB-N/P
- HSL-DO32-DB-N/P